

PRODUCT UPDATE

VGREEN EVO® VARIABLE SPEED MOTOR

THE POWER BEHIND THE PUMP™
JUST GOT BETTER!

The VGreen Evo® variable speed motor, now with Century Connect™ technology, is a cost-effective replacement pool pump motor designed to provide pool owners with maximum savings over traditional single-speed motors.

The Century Connect functionality enables communication with most existing automation systems making the Century VGreen Evo motor even better as a universal, direct drop-in replacement for variable speed or single-speed pool pump motors.



NOW COMPATIBLE WITH POOL AUTOMATION SYSTEMS

Need Century Connect technology?

Look for this icon when purchasing the VGreen Evo product.

VGREEN EVO – The Ultimate Universal Replacement Pool Pump Motor

- Meets state efficiency standards for swimming pool replacement motors – compliant with California Code of Regulations, Title 20, section 1605.3 (g) (6) and Title 21 of the Official Compilation of Codes, Rules and Regulations of the State of New York, Section 509.23
- Easy communication with most pool automation systems simple plug and play design that maintains automation system functionality
- **Simplified user interface** easy programming and user interface all with the push of a button

- **Direct drop-in replacement motor** available in both square flange and C-Face mounting
- Protects against harsh conditions to extend motor life – resistant to wind, water, weather, and UV with IPX5 moisture intrusion rating
- Higher efficiency, lower operating costs preprogrammed variable speed operating schedules allow users to best optimize their motor to minimize energy consumption intrusion rating

THP	RPM	VOLTAGE	AMPS	SERVICE FACTOR	FLANGE	APPROX "AG"	VGREEN EVO MOTOR STOCK NUMBER
1.30	600-3450	230/115	8.6/15.6	1.0	Square	11.83	EVQ130
1.65*	600-3450	230/115	10.5/17.7	1.0	Square	11.83	EVQ165
2.25*	600-3450	230/115	13.5/17.4	1.0	Square	11.83	EVQ225
1.30	600-3450	230/115	8.6/15.6	1.0	C-Face	12.04	EVC130
1.65*	600-3450	230/115	10.5/17.7	1.0	C-Face	12.04	EVC165
2.25*	600-3450	230/115	13.5/17.4	1.0	C-Face	12.04	EVC225

*When motor is running at 115VAC the total horsepower is 1.50 THP.



VGREEN EVO® VARIABLE SPEED MOTOR

NOW WITH CENTURY CONNECT™ TECHNOLOGY
THE NEW STANDARD FOR UNIVERSAL POOL REPLACEMENT MOTORS

NEW MOTOR FEATURE - CENTURY CONNECT™ TECHNOLOGY

The Century Connect technology enables the VGreen Evo motor to communicate with any compatible automation system. The simple plug and play design reduces the need for multiple points of control across various types of pool equipment. Check our website for compatible automation systems.

FEATURES

- Rotation: CCWPE
- TEFC Design
- Single Phase
- Class F Insulation
- 303 Stainless Steel Shaft
- Sealed Ball Bearings
- 50/60 Hz
- 50°C Ambient
- Dual Voltage 230/115 VAC, with Automatic Voltage Detection
- Variable Speed Operation (600-3450 RPM)
- Century Connect technology communicates with automation systems
- Freeze Protection

PUMP MANUFACTURER	PUMP MODELS	FULL RATE	UP RATE	TOTAL HORSEPOWER (THP)	VGREEN EVO° MOTOR MODEL REPLACEMENT	COMPATIBLE AUTOMATION SYSTEM
	WhisperFlo®* Max-E-Pro®*	0.50	0.75	0.95	EVQ130	EasyTouch®* Intellitouch®* Intelliconnect*
Pentair®* /	SuperFlo®* SuperMax®*	0.75	1.00	1.25	EVQ130	
StaRite®*	Challenger*	1.00	1.50	1.65	EVQ165	
Stanite	Dura-Glas™* Dura-Glas II*	1.50	2.00	2.25	EVQ225	
	Max-E-Glas™* Max-E-Glas II*	2.00	2.50	2.60	EVQ225**	
	O Face (Daniel Flance)	0.50	0.75	0.80	EVC130	OmniLogic®* ProLogic®* OmniPL™* EcoStar®*◊
	C-Face (Round Flange)	0.75	1.00	1.10	EVC130	
	Super Pump®* Super II™*	1.00	1.50	1.50	EVC165	
	MaxFlo TM *	1.50	2.00	2.25	EVC225	
11	IVIAXI IO	2.00	2.50	2.75	EVC225**	
Hayward®*	0 51	0.50	0.75	0.80	EVQ130	
	Square Flange	0.75	1.00	1.10	EVQ130	
	MaxFlo IITM*	1.00	1.50	1.50	EVQ165	
	MaxFlo XL TM *	1.50	2.00	2.25	EVQ225	
	Tristar™*	2.00	2.50	2.75	EVQ225**	
		0.50	0.75	0.95	EVQ130	iQPump* 1.0
	FloPro™*	0.75	1.00	1.25	EVQ130	Aqualink* TCX
Jandy®*	PlusHP TM *	1.00	1.50	1.65	EVQ165	iAqualink* 3.1 Aqualink* RS
	Stealth™*	1.50	2.00	2.25	EVQ225	
		2.00	2.50	2.60	EVQ225**	JEP-R*◊

^{**}VGreen Evo motor will derate at full speed setting

♦Denotes that the system connection capabilities are limited to the pump user interface only.



Power Efficiency Solutions Regal Rexnord

Customer Service: 1-833-Regal00 Email: pooldist@regalrexnord.com

pool-motors.com



The proper selection and application of products and components, including assuring that the product is safe for its intended use, are the responsibility of the customer. To view our Application Considerations, please visit https://www.regalrexnord.com/Application-Considerations. To view our Standard Terms and Conditions of Sale, please visit https://www.regalrexnord.com/Application-Conditions-of-Sale (which may redirect to other website locations based on product family).

*The following trademarks or trade names are believed to be the trademarks or trade names of their indicated owners and are not controlled by Regal Rexnord Corporation: Hayward, SuperPump, Super II, MaxFlo, Omnilogic, ProLogic, OmniPL, EcoStar and Tristar – Hayward Industries, Inc.; Jandy, FloPro, PlusHP, iQPump, Aqualink, iAqualink, JEP-R and Stealth – Zodiac International, S.A.S.U.; Pentair, StaRite, Challenger, Dura-Glas, Max-E-Glas, WhisperFlo, Max-E-Pro, SuperFlo, SuperMax EasyTouch, Intellitiouch and Intelliconnect – Pentair, Inc.; Pool & Hot Tub Alliance – The Association of Pool and Spa Professionals Corp..

"Regal Rexnord" is not indicative of legal entity. Refer to product purchase documentation for the applicable legal entity. Regal Rexnord, Century, Century Connect, The Power Behind the Pump and VGreen Evo are trademarks of Regal Rexnord Corporation or one of its affiliated companies.

© 2021, 2023 Regal Rexnord Corporation, All Rights Reserved. MCSSP23034E • Form# C0069E • R18



For more information on the VGreen Evo® motor with Century Connect™ technology, scan the QR code.



